



- True double-conversion
- Microprocessor control optimizes reliability
- Input power factor correction
- Output power factor 0.8
- Wide input voltage (110 V – 300 V)
- Converter mode available
- ECO mode for energy saving
- Generator compatible
- Charger capacity expansion to 6A for long-run models
- Smart SNMP works well with either USB or RS-232 together
- Comprehensive display allows easy monitoring and access of UPS status

MODEL		GH11-1K (L)	GH11-2K (L)	GH11-3K (L)
PHASE		Single phase with ground		
CAPACITY		1000 VA / 800 W	2000 VA / 1600 W	3000 VA / 2400 W
INPUT				
Nominal Voltage		100/110/115/120/127VAC or 200/208/220/230/240VAC		
Input Voltage Range		55-145 VAC or 110-300 VAC		
Frequency Range		40Hz ~ 70 Hz		
Power Factor		≥0.99 @ Nominal Voltage (100% load)		
OUTPUT				
Output Voltage		100/110/115/120/127VAC or 200/208/220/230/240VAC		
Voltage Regulation		± 1%		
Frequency Range (Synchronized Range)		47 ~ 53 Hz or 57 ~ 63 Hz		
Frequency Range (Batt. Mode)		50 Hz or 60Hz ± 0.1 Hz		
Current Crest Ratio		3:1		
Harmonic Distortion		≤ 3 % THD (Linear Load)	≤ 6 % THD (Non-linear Load)	
Transfer Time	AC to DC	Zero		
	Inverter to Bypass	4 ms (Typical)		
Waveform (Batt. Mode)		Pure Sinewave		
EFFICIENCY				
To AC Mode		88%	89%	90%
To Battery Mode		83%	87%	88%
Standard Model	Battery Type	12 V / 9 AH	12 V / 9AH	12 V / 9 AH
	Numbers	2	4	6
	Typical Recharge Time	4 hours recover to 90% capacity		
	Charging Current (max.)	1.0 A		
Long-run Model	Charging Voltage	27.4VDC ± 1%	54.7 VDC ±1%	82.1 VDC ±1%
	Battery Type	Depending on the capacity of external batteries		
	Numbers	3	6	8
	Charging Current (max.)	1.0A/2.0A/4.0A/6.0 A		
	Charging Voltage	41.0VDC ± 1%	82.1 VDC ±1%	109.4VDC ±1%
INDICATORS				
LCD		Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators		
ALARM				
Battery Mode		Sounding every 4 seconds		
Low Battery		Sounding every second		
Overload		Sounding twice every second		
Fault		Continuously sounding		
PHYSICAL				
Standard Model	Dimension, D x W x H (mm)	285*145*220	395*145*240	415*190*337
	Net Weight (kgs)	9.3	18.6	30
Long-run Model	Dimension, D x W x H (mm)	282 x 145 x 220	397 X 145 X 220	
	Net Weight (kgs)	4.6	6.8	7.4
ENVIRONMENT				
Humidity		20-90 % RH @ 0- 40°C (non-condensing)		
Noise Level		Less than 50dBA @ 1 Meter		
MANAGEMENT				
Smart RS-232/USB		Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC		
Optional SNMP		Power management from SNMP manager and web browser		

Product specifications are subject to change without further notice

E-mail:manager@santakpower.com.cn

Http://www.skepower.com